






Lok






Structure



Shelves



Doors





LOCKERS



STRUCTURE



Top and bottom: 25 mm of thickness. Recoated chipboard with melamine of 120 grs/m² in both faces with a density of 600 Kg/m³ ± 5 %. ABS edges have a bevel of 0,8 mm. Edges are fixed with melted glue and rounded in shape. Front edge has a bevel of 2 mm.



Single or multi-tops are available.



Bottom includes 4 metal levelers with a polypropylene cover.



Sides: 19 mm of thickness. Recoated chipboard with melamine of 120 grs/m² in both faces with a density of 600 Kg/m³ ± 5 %. ABS edges have a bevel of 0,8 mm. Edges are fixed with melted glue and rounded in shape. Upper and lower part of sides are without bevel.



The distance between drilled-holes is 32 mm. Shelves can be fixed in any position. Useful locker-hole height is 400 mm.



Shelves: 25 mm of thickness. Recoated chipboard with melamine of 120 grs/m² in both faces with a density of 600 Kg/m³ ± 5 %. ABS front edges have a bevel of 2 mm. The rest of edges are without bevel.



Back panel: 19 mm of thickness. Recoated chipboard with melamine of 120 grs/m² in both faces with a density of 600 Kg/m³ ± 5 %. ABS edges have a bevel of 0,8 mm. Edges are fixed with melted glue and rounded in shape.







All components include fast-fixing screws and eccentrics to be assembled.

Flush-assembly to the structure.

Finishes: silver, graphite, white, grey, beech, maple, pear, wengue, light acacia, dark acacia, black, oak or dark oak.



This unit is delivered ASSEMBLED.



HINGED DOORS



19 mm of thickness. Recoated chipboard with melamine of 120 grs/m² in both faces with a density of 600 Kg/m³ ± 5 %. ABS edges have a bevel of 2 mm. Edges are fixed with melted glue and rounded in shape. **110° door hinge** with silicone door-protections (stoppers).



OPTIONAL: mail-hole available for the doors.

Finishes: silver, graphite, white, grey, beech, maple, pear, wengue, light acacia, dark acacia, black, oak or dark oak.

Other finishes with soft texture and matt-gloss

- Black: Pantone Black C / Ral 9004
- Gray: Pantone Cool gray 5C / Ral 7004
- Yellow: Pantone 123C / Ral 1021
- Turquoise green: Pantone 2247C / Ral 6019
- Green: Pantone 376C
- Orange: Pantone 1575C / Ral 2003
- Red: Pantone 180C / Ral 3020
- Blue: Pantone 7455C / Ral 5002



LOCK TYPES



KEY: hook locking system. Master key or same keys options are available.




4-DIGIT LOCK: horizontal hook locking system. It needs 4-digit combination to open the door. Black finish.



RFID CARD: clutch locking system. It needs the proximity of the card to open the door (3 digit max). Silver handle and black cover finishes.
Technology: Mifare 1K / 13.56MHz.



ELECTRONIC: vertical hook locking system. It needs 6-digit code to open the door. Black finish.



OPTIONAL COMPLEMENTS

Lok

EXTRA SHELVES



25 mm of thickness. Recoated chipboard with melamine of 120 grs/m² in both faces with a density of 600 Kg/m³ ± 5 %. ABS front edges have a bevel of 2 mm. The rest of edges are without bevel.



Only for lockers without **mail-hole door**.

Finishes: silver, graphite, white, grey, beech, maple, pear, wengue, light acacia, dark acacia, black, oak or dark oak.



MULTI-TOP



25 mm of thickness. Recoated chipboard with melamine of 120 grs/m² in both faces with a density of 600 Kg/m³ ± 5 %. ABS edges have a bevel of 0,8 mm. Edges are fixed with melted glue and rounded in shape. Front edge has a bevel of 2 mm.



Only for lockers **without top**.



USER LABEL IDENTIFIER

Blue polypropylene sticker 120 x 45 mm



KNOB

Zamak-knob finish in black epoxy matte paint.

Size: 15 x 15 x 25 mm

Can be assembled with a M4 screw and a Ø5 mm hole.



HANDLE

For 4-digit lock.

Black polypropylene.

Size: 92,9 x 29,5 mm





WARDROBE CABINET

Lok



STRUCTURE



Top and bottom: 25 mm of thickness. Recoated chipboard with melamine of 120 grs/m² in both faces with a density of 600 Kg/m³ ± 5 %. ABS edges have a bevel of 0,8 mm. Edges are fixed with melted glue and rounded in shape. Front edge has a bevel of 2 mm.



Single top.



Bottom includes 4 metal levelers with a polypropylene cover.



Sides: 19 mm of thickness. Recoated chipboard with melamine of 120 grs/m² in both faces with a density of 600 Kg/m³ ± 5 %. ABS edges have a bevel of 0,8 mm. Edges are fixed with melted glue and rounded in shape. Upper and lower part of sides are without bevel.



The distance between drilled-holes is 32 mm. Shelves can be fixed in any position.



Divider shelf: 25 mm of thickness. Recoated chipboard with melamine of 120 grs/m² in both faces with a density of 600 Kg/m³ ± 5 %. ABS front edges have a bevel of 2 mm. The rest of edges are without bevel.



Back panel: 19 mm of thickness. Recoated chipboard with melamine of 120 grs/m² in both faces with a density of 600 Kg/m³ ± 5 %. ABS edges have a bevel of 0,8 mm. Edges are fixed with melted glue and rounded in shape.



All components include fast-fixing screws and eccentrics to be assembled.

Flush-assembly to the structure.

Finishes: silver, graphite, white, grey, beech, maple, pear, wengue, light acacia, dark acacia, black, oak or dark oak.



Telescopic hanger: For clothes. Chrome finish.



This unit is delivered ASSEMBLED.







MEASUREMENTS (cm)

Lok


LOCKER WITH MAIL-HOLE:




INNER MEASUREMENTS:




LOCKER WITHOUT MAIL-HOLE:



INNER MEASUREMENTS:



WARDROBE CABINET:





FINISHES



MELAMINE



TEXTURED MELAMINE



MELAMINE





VERSIONS



SINGLE-COLOR

WITH MAIL-HOLE DOOR:



WITH DOOR:



WARDROBE CABINET:



MULTICOLOR

WITH MAIL-HOLE DOOR:



WITH DOOR:





CARE INTRUCTIONS

Clean the locker and its components with a soft cloth and neutral detergent.



RECYCLABILITY AND TOXIC MATERIALS

This locker does not contain any toxic material and its components are recyclable.



MATERIALS:

- 41% of this table materials are recycled.
- 97% of the material is melamine chipboard.



PRODUCTION:

- Components and manufacturer packs are optimized to avoid chipboard remnant waste.
- Production processes are optimized using fewer natural resources.



SHIPPING:

- Furniture is delivered with our trucks. Routes are optimized to reduce CO₂ emissions.
- Truck drivers are trained to drive efficiently and respectful with environment.



USE:

- All kind of replacements are available. It is the better way to prolong its utility.
- User document can be downloaded from www.mobellinea.es clicking on Eco Design link.



END OF LIFE:

- This lockers are recyclable in a 97 %.
- Locker packing materials are 100 % recyclables.
- Different components can be checked in the materials' recycle document in www.mobellinea.es clicking on Eco Design link.

