



DESKTOPS

 **Melamine top:** 25 mm of thickness. Recoated chipboard with melamine of 120 grs/m² in both faces with a density of 600 Kg/m³ ± 5 %. ABS edges all around the top with a bevel of 2 mm. Edges are fixed with melted glue and rounded in shape.

Finishes: graphite, white, grey, beech, maple, pear, wengue, light acacia, dark acacia, black, oak or dark oak.

 **HPL (High Pressure Laminate) top:** 25 mm of thickness. Recoated chipboard with decorative plastic laminate of 0,8 mm of thickness with a density of 600 Kg/m³ ± 5 %. ABS edges all around the top with a bevel of 2 mm. Edges are fixed with melted glue and rounded in shape.

Finishes: graphite, white, grey, beech, maple, pear, wengue, light acacia, dark acacia, black, oak or dark oak.



Tops are fixed to the structure of the table with DIN 912 M6 x 14 black screws.

5 cm round edges.





FRAME



V-SHAPE FRAME



Steel cold laminated beams that consist in 2 round columns ($\varnothing 30 \times 2$ mm), 1 rectangular cross-beam for the top ($50 \times 30 \times 2$ mm), 1 round cross-beam for the columns ($\varnothing 30 \times 2$ mm) and 2 calibrated tubes ($\varnothing 8$ mm).






Curved columns are welded and embedded to the rest of the structure with MIG-system.



In the lower side of the frame there are PP black levelers with spherical roller bearing (M8, $\pm 1,5$ cm height and 15° tilted).




Available finishes: silver epoxy paint (RAL 9006), white (RAL 9016), graphite (RAL 7022) or black (RAL 9005).



Reinforcement beam to fix both sides: round steel tube of $\varnothing 22 \times 2$ mm. Same finishes of the structure.



Are embedded to the structure.





FRAME



PROP-SHELF

Melamine top: 25 mm of thickness. Recoated chipboard with melamine of 120 grs/m² in both faces with a density of 600 Kg/m³ ± 5 %. ABS edges all around the top with a bevel of 2 mm. Edges are fixed with melted glue and rounded in shape.

Finishes: graphite, white, grey, beech, maple, pear, wengue, light acacia, dark acacia, black, oak or dark oak.

Stratified top: 25 mm of thickness. Recoated chipboard with stratified of 0,8 mm of thickness with a density of 600 Kg/m³ ± 5 %. ABS edges all around the top with a bevel of 2 mm. Edges are fixed with melted glue and rounded in shape.

Finishes: graphite, white, grey, beech, maple, pear, wengue, light acacia, dark acacia, black, oak or dark oak.



Prop-shelf is fixed to the structure of the table with DIN 912 M6 x 14 black screws.



Prop-shelf reinforcement beam: round steel tube of Ø22 x 2 mm.

Same finishes of the structure.




Is embedded to the structure and fixed with DIN 912 M6 x 14 black screws.





MEASUREMENTS (cm)


TABLES WITH ROUND EDGES:



FINISHES



MELAMINE DESKTOPS



TEXTURED MELAMINE DESKTOPS



METAL FRAME

