



PROTECTION SCREENS

WITH METHACRYLATE SUPPORT









3 mm extruded clear-methacrylate sheet (PMMA) with rounded and polished edges.









Two methacrylate-triangular supports of 3 mm.



Fixed supports: **CAN NOT** be moved to right or left sides.



MEASUREMENTS (cm)





PROTECTION SCREENS

WITH METAL SUPPORT






5 mm extruded clear-methacrylate sheet (PMMA) with rounded and polished edges.






Two steel-round supports available in silver (RAL 9006) finish.



Supports: **CAN** be moved to right or left sides.






Metal support




Metal support



MEASUREMENTS (cm)



Non-slip plastic





PROTECTION SCREENS

METHACRYLATE ADD-ON



6 mm extruded clear-methacrylate sheet (PMMA) with rounded and polished edges.



Support system with aluminium brackets painted in silver epoxy paint (RAL 9006), white (RAL 9016), graphite (RAL 7022) or black (RAL 9005).

Inside the bracket there is the steel reducer for methacrylate.





Can be assembled on melamine or upholstered 1 level screens.



Can not be assembled on acoustic screens.



Supports: **CAN** be moved to right or left sides.



Thickness 25 mm




Thickness 19 mm



Bracket




Reducer




MEASUREMENTS (cm)

FRONT SCREENS:



SIDE SCREENS:





PROTECTION SCREENS

METHACRYLATE FRONT SCREENS



6 mm extruded clear-methacrylate sheet (PMMA) with rounded and polished edges.



Support system with aluminium brackets painted in silver epoxy paint (RAL 9006), white (RAL 9016), graphite (RAL 7022) or black (RAL 9005).


Inside the bracket there is the steel reducer for methacrylate.




OTHER RANGES: Supports **CAN** be moved to right or left sides.

STAR and BORN: Fixed supports **CAN NOT** be moved to right or left sides.


OTHER RANGES: Fixed to the desktop.




STAR - INDIVIDUAL DESKS: Fixed to the frame of the desk.



STAR y BORN - FACE to FACE DESKS: Fixed to the frame of the desk.



MEASUREMENTS (cm)





PROTECTION SCREENS

METHACRYLATE ADD-ON FOR LIGHTING



6 mm extruded clear-methacrylate sheet (PMMA) with rounded and polished edges.



Support system with aluminium brackets painted in silver epoxy paint (RAL 9006), white (RAL 9016), graphite (RAL 7022) or black (RAL 9005).


Inside the bracket there is the steel reducer for methacrylate.




Fixed supports **CAN NOT** be moved to right or left sides.




Fixed to the frame of the desk.





=



+



MEASUREMENTS (cm)



PROTECTION SCREENS

HANGING



4 mm extruded clear-methacrylate sheet (PMMA) with rounded and polished edges.



Fixed supports **CAN NOT** be moved to right or left sides.




Lengths 180, 160, 140, 120 and 80 cm.




FOR CONCRETE-STEEL CEILING: For concrete, brick, or steel ceilings.

- 2 or 3 ceiling nickel-supports.
- 2 or 3 steel-cables of Ø1,2 mm and 2 meters large.
- 2 or 3 *auto grip* hooks.
- 2 or 3 threaded-studs and screws.



FOR SUSPENDED CEILING: holes through the ceiling are not needed.

- 2 or 3 steel-clips of 20 mm.
- 2 or 3 steel-cables of Ø1,2 mm and 3 meters large.
- 2 or 3 *auto grip* hooks.





CERTIFICATES

Methacrylate: ISO 7823-2:2003



UL 94 HB (Horizontal Burning). Slow horizontal burn test (HB) is considered “self-extinguishing”. The lowest (least flame retardant) UL94 rating.



UNE-EN 13501 - Class “E”



CARE INTRUCTIONS

Clean with a soft cloth and neutral detergent.

